


Accelerator Performance and New Developments N. Angert, GSI


- Ion Sources
- Unilac
- SIS18






LEBT-Section







LEBT/RFQ Transmission



UH3DT2: 2 mA/div (~3 mA)

UH1DT1: 5 mA/div (~8 mA)

UL5DT8: 5 mA/div (~10 mA)


UL4DT4: 10 mA/div (~24 mA)

20 Dez 2001 02:40:42




Modifications of the Ion Source


- using more stable grids within the ion source
 - \Rightarrow life time and pulse stability
- increase of the arc current from 300 A to 800 A
 - ⇒ pulse stability and noise reduction
- optimization of the extraction system (material, geometry)
 - ⇒ extractable current and availability
- glueing of the cathodes (carbonized glue)
 - \Rightarrow pulse stability
- use of one titanium cathode to start with better vacuum
 - ⇒ reliability, reaching faster good performance






Particle transmission Poststripper-Transfer line






SIS Intensities








Maximum Intensity with Gold Ions



SIS Intensities







Development of SIS18

- 1.3 T/s → 4 T/s aim (1 Hz)
 June 2001 test with 25 MW pulse load/industrial customers; still interferences
 Solution: separate GSI 110 kV connection to 380 kV possible rearrangement in connection with airport extension could provide free 110 kV line
- new slow extraction mode with rf-noise voltage provides excellent position stability during spill

February 21, 2002 N. Angert 12



Summary

- Big step in MEVVA ion source performance towards routine operation
- But noise reduction still needed
- Bottle necks
 - 1. preacceleration
 - 2. matching to RFQ
 - 3. matching to Alvarez section
- 10¹⁰ particles/spill aim for 2002
- Machine development time needed to achieve argon beam transmission with uranium beam